

## Product Profile

- Choice of portable, fixed mount, or wall mount configurations
- Wireless printing via optional Bluetooth™ 700 Series Holder or CK60 Series for portable and fixed mount configurations
- Easy loading of up to 3-ply paper from internal or external paper trays
- 512k flash memory can store DBCS fonts such as Korean and Chinese
- Optional HHC holders and docks for Intermec® 700, 6220 and CK60 Series mobile computers
- Fast two-page-per-minute print time helps get the work done fast



### 6 8 2 0 P R I N T E R

The Intermec® 6820 printer produces high-quality customer invoices, receipts, load reports, transfers and other documents for route accounting applications. The real time accounting structure provided by the 6820 printer and Intermec handheld computers facilitates route delivery settlement and ensures customer information is always current.

Customers have the choice of portable, fixed mount, and wall mount configurations depending on mobility requirements.

#### Portable

The Intermec 6820 portable printer provides flexibility and mobility. It features a handle for easy carrying and a compact tray which holds enough paper for an entire day. A seat-mount strap is available to secure the printer in vehicles with bench seats. An optional, soft-sided carrying case provides a sealed compartment inside the case cover for storage of invoices.

#### Fixed Mount

The fixed mount model is ideal for applications where mounting the printer in a vehicle is preferred. The mobile computer holder can be mounted either to the side of the printer or remote from the printer, whichever is most convenient. Although the printer is safely mounted to the vehicle, a quick release feature allows one-step removal of the printer for swapping from one vehicle to another.

#### Wall Mount

The wall mount printer can be mounted on rugged vertical surfaces in trucks and settlement rooms. It is ideal for installations where space is limited. A quick release allows one-step removal for swapping from one vehicle to another. Optional paper trays hold paper for multiple route days.

**Application**

Portable dot matrix receipt printer

**Portable**

Optional handle, AC foot, Intermec® 700, 6220 and CK60 Series terminal holder top mount.

**Physical Characteristics**

**Standard:** Handle, 62xx holder top mount or fill plate

**Length:** 38.1cm (15")

**Width:** 41.9cm (16.5")

**Depth:** 13cm (5.13")

**Weight:** 5.67kg (12.25 lbs.)

**Portable with AC Foot****Physical Characteristics**

**Length:** 38.1cm (15")

**Width:** 48.3cm (19")

**Depth:** 13cm (5.13")

**Weight:** 5.67kg (12.25 lbs.)

**Wall Mount****Physical Characteristics**

**Length:** 26.7cm (10.5")

**Width:** 33.7cm (13.25")

**Depth:** 11.4cm (4.5")

**Weight:** 6.42kg (14.15 lbs.)

**Fixed Mount**

- Base is 32.5cm (12.75") x 35.5cm (14"). The upper portion may include the 62xx terminal holder.
- Refer to the 6820 printer user's guide (961-019-013) for specific configurations for the following:
  - Custom with Intermec® 700, 6220 and CK60 Series terminal holder top mount

**Physical Characteristics**

**Length:** 36.8cm (14.5")

**Width:** 47cm (18.5")

**Depth:** 20.3cm (8")

**Weight:** 6.55kg (14.4 lbs.)

**Operating Environment**

**DC Operating Temperature:**

-20° to 60°C (-4° to 140°F)

**AC Operating Temperature:**

-20° to 45°C (-4° to 113°F)

**Storage Temperature:**

-30° to 70°C (-22° to 158°F)

**Power Supply**

**Vehicle:** low amperage draw; protection from voltage irregularities

**Lead Acid Battery:** 12-volt standard cam-corder type. Full charge will print dozens of tickets. Time to recharge is one hour.

**AC Adapter:** 115/230 volt

**Print Specifications**

**Characteristics:** Dot matrix, Bi-directional, Graphics capable

**Print speed:** 2 pages per minute

**Print width (min / max):** 7.5 inch / 8.5 inch

**Type styles:** char/line: Normal 80, Bold 40, Condensed 136, Bold condensed 68

**Paper**

1 to 3-ply fan fold, 7.5" to 8.5" x 11", Carbonless, NCR paper with adhesive tacking on left border

**Ribbon**

- One color cartridge, black, 2,250,000 character life
- One color cartridge, purple, 3,750,000 character life

**Regulatory Approvals**

FCC Class B, CE mark

**Option**

- 6820 Developers Kit

**Note**

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**  
9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
Mississauga, Ontario  
L5S 1M2 Canada  
tel: 905.673.9333  
fax: 905.673.3974

**Europe/  
Middle East & Africa  
Headquarters**

Reading International Business Park  
Basingstoke Road  
Reading RG2 6DD  
United Kingdom  
tel: 44.118.923.0800  
fax: 44.118.923.0801

**Asia**

**Asia Regional Office**  
26-16 International Plaza  
10 Anson Road  
Singapore 079903  
tel: 65.6324.8391  
fax: 65.6324.8393

**Beijing Representative Office**

29 FL, Unit A1, China Merchant Tower  
118 Jian Guo Road  
Chaoyang District, Beijing 100022  
Tel: 86.10.5165.5922  
Fax: 86.10.6567.6778

**Australia**

Level 4, 1-3 Atchison Street  
St. Leonards, NSW 2065  
Australia  
tel: 61.2.9330.4400  
fax: 61.2.9437.0204

**South America & Mexico**

**Intermec South America Ltda.**  
Rua Samuel Morse 120 9 andar  
Brooklin CEP04576-060  
São Paulo, SP  
Brazil  
tel: 55.11.5502.6770

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa  
Mexico, DF, 06140 Mexico  
tel: 525.55.241.4800  
fax: 525.55.211.8121

**Internet**

www.intermec.com

**Sales**

800.934.3163  
(toll free in N.A.)  
tel: 425.348.2726

**OEM Sales**

tel: 425.348.2762

**Customer Service and  
Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2006 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608961-01E 03/06

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.